

INDUSTRIAL COMPONENT DATA

M30C-FL-Y-* 183291 Y7-183291 EATON ELECTRIC Indicator light, Flat Front, flush, yellow, individual facility ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FL-Y-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FL-Y-*
Catalog number	Y7-183291
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-36AFE90A83
Generated	2026-08-03

Product Overview

Indicator light, Flat Front, flush, yellow, individual facility for inscription

M30C-FL-Y-*

Indicator light, RMQ-Titan, Flat, yellow, individual facility for inscription, Metal bezel

Indicator light, Product range: RMQ-Titan, Single unit, Design: Flat, Color Lens: yellow, Button plate individual facility for inscription, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Indicator light, RMQ-Titan, Flat, yellow, individual facility for inscription, Metal bezelIndicator light, Product range:

RMQ-Titan, Single unit, Design: Flat, Colour Lens: yellow, Button plate individual facility for inscription, Degree of Protection: IP66, IP67, IP69K, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Standards: IEC/EN 60947, VDE 0660Delivery program

Product rangeFlat Front (drilling dimensions 30.5 mm)Basic functionIndicator lightsMounting hole diameter [?]30.5

mmSingle unit/Complete unitSingle unitDesignFlatColourLensyellowLensButton plateindividual facility for inscriptionDegree

of ProtectionIP66, IP67, IP69Front ringMetal bezelConnection to SmartWire-DTyes

with SWD-RMQ connectionsTechnical data

GeneralStandardsIEC/EN 60947

VDE 0660Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66, IP67, IP69 Ambient temperature Open-25 - +70 °C Mounting position As required Mechanical shock resistance not planned g Terminal capacities Solid 0.5 - 1.5 mm² Terminal capacities Stranded 0.5 - 1.5 mm² shipping classification DNV
GL Contacts Rated impulse withstand voltage [U_{imp}] 4000 V AC Rated insulation voltage [U_i] 250 V Overvoltage category/pollution degree III/3 Design verification as per IEC/EN 61439
Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Front element for indicator...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FL-Y-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.