

INDUSTRIAL COMPONENT DATA

M30C-FR22K 187036 Y7-187036 EATON ELECTRIC Potentiometer, Flat Front, R 22 kOhm

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FR22K



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FR22K
Catalog number	Y7-187036
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-62A58CD8FB
Generated	2026-08-04

Product Overview

Potentiometer, Flat Front, R = 22 kOhm

M30C-FR22K

Potentiometer, flat front, M30, 30.5 mm, R 22 k?, P 0.5 W, Metal bezel

Potentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Impedance: R= 22 k?, Rated power: P= 0.5 W, Degree of Protection: IP66, Metal bezel, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Potentiometer, flat front, M30, 30.5 mm, R 22 k?, P 0.5 W, Metal bezelPotentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Impedance: R= 22 k?, Rated power: P= 0.5 W, Degree of Protection: IP66, Metal bezel, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

General specificationsProduct nameEaton Moeller® series M30 PotentiometerPart

no.M30C-FR22KEAN4015081821020Product Length/Depth36 millimetreProduct height63 millimetreProduct width46 millimetreProduct weight0.055 kilogramCertificationsVDE 0660

IEC/EN 60947Product TradenameM30Product TypePotentiometerProduct Sub TypeNoneFeatures & FunctionsBezel colorTitaniumDesignFlat frontElectric connection typeScrew connectionFitted with:3 individual screw terminalsGeneral informationAccuracy $\pm 10\%$ (linear), Resistance valueDegree of protectionIP66

NEMA OtherLifespan, mechanical25,000 OperationsOpening diameter30 mmOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)4000 V ACTypePotentiometerAmbient conditions, mechanicalMounting positionAs requiredShock resistanceNot plannedClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max70 °CClimatic proofingDamp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30Terminal capacitiesTerminal capacity (solid)0.5 - 1.5 mm²Termi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FR22K with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.