

INDUSTRIAL COMPONENT DATA

M30C-FR2K2-BLANK 187039 Y7-187039 EATON ELECTRIC Potentiometer, Flat Front, without scale/inscription, R 2.2..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FR2K2-BLANK



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FR2K2-BLANK
Catalog number	Y7-187039
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-BA8173F107
Generated	2026-08-03

Product Overview

Potentiometer, Flat Front, without scale/inscription, R = 2.2 kOhm

M30C-FR2K2-BLANK

Eaton Moeller® series M30 Potentiometer, flat front, M30, 30.5 mm, Without scale/inscription, R 2.2 k?, P 0.5 W, Metal bezel

Potentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Without scale/inscription, Impedance: R= 2.2 k?, Rated power: P= 0.5 W, Degree of Protection: IP66, Metal bezel, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Potentiometer Catalog Number 187039 Model Code M30C-FR2K2-BLANK EAN 4015081821051 Product Length/Depth 36 mm Product Height 63 mm Product Width 46 mm Product Weight 0.055 kg

Certifications VDE 0660

IEC/EN 60947 Catalog Notes Without scale/inscription Features & Functions

Bezel color Titanium Design Flat front Electric connection type Screw connection Fitted with: 3 individual screw terminals

General

Accuracy $\pm 10\%$ (linear), Resistance value Degree of protection IP66

NEMA Other Lifespan, mechanical 25,000 Operations Opening diameter 30 mm Overvoltage category III Pollution degree 3
Rated impulse withstand voltage (Uimp) 4000 V AC Type Potentiometer Ambient conditions, mechanical
Mounting position As required Shock resistance Not planned Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Terminal capacities
Terminal capacity (solid) 0.5 - 1.5 mm² Terminal capacity (stranded) 0.5 - 1.5 mm² Tightening torque 0.5 Nm, Screw
terminals Electrical rating
Power consumption 0.5 W Rated insulation voltage (Ui) 250 V Rated power 0.5 VA Resistance 2200 Ohm Communication
Connection to SmartWire-DT No Design verification
Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole,
current-dependent Pvid 0 W Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FR2K2-BLANK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.