

INDUSTRIAL COMPONENT DATA

M30C-FW3 187089 Y7-187089 EATON ELECTRIC Changeover switches, Flat Front, with rotary head, labeled, 3 posit..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FW3



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FW3
Catalog number	Y7-187089
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-27B2B9B7AC
Generated	2026-08-03

Product Overview

Changeover switches, Flat Front, with rotary head, labeled, 3 positions, momentary
M30C-FW3

Changeover switch, RMQ-Titan, With rotary head, momentary, 3 positions, inscribed, Metal bezel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: With rotary head, momentary, 3 positions, inscribed, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, with plunger bridge for the middle contact, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 187089 Model Code M30C-FW3 EAN 4015081821464 Product Length/Depth 36 mm Product Height 43 mm Product Width 46 mm Product Weight 0.042 kg

Certifications IEC/EN 60947

VDE 0660

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified Features & Functions
Bezel color Titanium Bezel material Metal Design With rotary head
Flat front Fitted with: Plunger bridge for the middle contact
Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Inscription Inscribed
General
Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations
Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III
Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 40 ° Type Selector switch
actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min
40 °C Ambient storage temperature - max 80 °C Climatic proofing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FW3 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.