

INDUSTRIAL COMPONENT DATA

M30C-FWJS2H 197526 Y7-197526 EATON ELECTRIC

M30C-FWJS2H

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWJS2H



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWJS2H
Catalog number	Y7-197526
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-C9C098DBC7
Generated	2026-08-05

Product Overview

M30C-FWJS2H

Joystick, Flat Front (drilling dimensions 30.5 mm), horizontally momentary, with metal shaft, 2 positions, Metal bezel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Joystick Catalog Number 197526 Model Code M30C-FWJS2H EAN 4015081941070 Product Length/Depth 36 mm Product Height 93 mm Product Width 46 mm Product Weight 0.06 kg

Certifications VDE 0660

UL Category Control No.: NKCR

DNV

GL

CSA File No.: 012528

UL File No.: E29184

IEC/EN 60947

UL 508

CSA-C22.2 No. 94-91

CSA Class No.: 3211-03

IEC/EN 60947-5

UL Listed

CSA certified

CSA-C22.2 No. 14-05

CE marking Features & Functions

Bezel color Chrome Bezel material Metal Fitted with: Filament bulb (24 V)

Retraction in 0-position

Front ring General

Degree of protection IP66

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 2000 Operations/h

Product Category RMQ-Titan Type Joystick Ambient conditions, mechanical

Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated operational current (Ie) at AC-21, 400 V, 415 V 0 A Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5 N Actuator function Momentary

Horizontal Number of actuation directions 2 Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-depende...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWJS2H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.