

INDUSTRIAL COMPONENT DATA

M30C-FWK 187103 Y7-187103 EATON ELECTRIC Changeover switches, Flat Front, with thumb-grip, 2 positions, mome..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWK



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWK
Catalog number	Y7-187103
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-86ED99F8E3
Generated	2026-08-05

Product Overview

Changeover switches, Flat Front, with thumb-grip, 2 positions, momentary
M30C-FWK

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, With thumb-grip, momentary, 2 positions, Metal bezel
Changeover switch, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, momentary, 2 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 187103 Model Code M30C-FWK EAN 4015081821556 Product Length/Depth 36 mm Product Height 47 mm Product Width 46 mm Product Weight 0.042 kg
Certifications IEC/EN 60947

VDE 0660 Features & Functions

Bezel color Titanium Bezel material Metal Design With thumb-grip Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations
Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III

Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 40 ° Type Selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuator color Black Actuator function Spring-return

Momentary Actuator type Toggle Number of switch positions 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.