

## INDUSTRIAL COMPONENT DATA

# M30C-FWR-\* 187105 Y7-187105 EATON ELECTRIC

## Changeover switches, Flat Front, with rotary head, individual fac..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWR-\*



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | M30C-FWR-*                        |
| Catalog number  | Y7-187105                         |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-FCE9E72858                     |
| Generated       | 2026-08-05                        |

### Product Overview

Changeover switches, Flat Front, with rotary head, individual facility for inscription, 2 positions, maintained M30C-FWR-\*

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, With rotary head, maintained, 2 positions, individual facility for inscription, Metal bezel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: With rotary head, maintained, 2 positions, individual facility for inscription, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Notes on customized inscription -> Data sheet, additional product information (links), Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 187105 Model Code M30C-FWR-\* Product Length/Depth 36 mm Product Height 43 mm Product Width 46 mm Product Weight 0.042 kg Certifications IEC/EN 60947 VDE 0660 Catalog Notes Notes on customized inscription -> Data sheet, additional product information (links) Features & Functions

Bezel color Titanium Bezel material Metal Design With rotary head Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Inscription Individual inscription possible General Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 60 ° Type Selector switch actuator Ambient conditions, mechanical Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Communication Connection to SmartWire-DT With SWD-RMQ connection...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWR-\* with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.