

INDUSTRIAL COMPONENT DATA

M30C-FWRK 187109 Y7-187109 EATON ELECTRIC

Changeover switches, Flat Front, with thumb-grip, 2 positions, mai..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWRK



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWRK
Catalog number	Y7-187109
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-DC4A16A2CC
Generated	2026-08-05

Product Overview

Changeover switches, Flat Front, with thumb-grip, 2 positions, maintained

M30C-FWRK

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, With thumb-grip, maintained, 2 positions, Metal bezel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, maintained, 2 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Changeover switch Catalog Number 187109 Model Code M30C-FWRK EAN 4015081821594 Product Length/Depth 36 mm Product Height 47 mm Product Width 46 mm Product Weight 0.042 kg

Certifications VDE 0660

IEC/EN 60947

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Product specifications

Type Selector switch actuator Actuator color Black Actuator function Maintained

Switching function latching Fitted with: Front ring Operating frequency 2000 Operations/h Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator type Toggle Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Ambient storage temperature - max 80 °C Ambient storage temperature - min 40 °C Force for positive opening - min 0 N Opening diameter 30 mm Opening height 0 mm Operating torque 0.3 Nm Switching angle 60 ° Width opening 0 mm Bezel color Titanium Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Bezel material Metal Design With thumb-grip

Flat front Mounting position As required Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Functions

Stay-put/spring-return function, can b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWRK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.