

INDUSTRIAL COMPONENT DATA

M30C-FWRS*-MS*-* 187093 Y7-187093 EATON ELECTRIC

Key-operated actuators, Flat Front, not suitable for master..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWRS*-MS*-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWRS*-MS*-*
Catalog number	Y7-187093
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-C077B987B0
Generated	2026-08-04

Product Overview

Key-operated actuators, Flat Front, not suitable for master key sys., 2/3 pos. selectable, maintained/momentary select., MS selectable, indiv. labeled

M30C-FWRS*-MS*-*

Eaton Moeller® series M30 Key-operated actuator, Flat Front, maintained, Select from 2 or 3 positions, MS1-MS20: Key withdrawable: Selectable, Metal bezel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, selectable, Not suitable for master key systems, selectable, Lock mechanism: selectable, individual facility for inscription, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Notes on customized inscription -> Data sheet, additional product information (links), Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 187093 Model Code

M30C-FWRS*-MS*-* Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg

Certifications CSA Class No.: 3211-03

CSA file No. 012528

DNV
GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
CE marking
UL Category Control No.: NKCR
UL File No.: E29184
UL Listed
CSA certified
ETIM for 187093 Low-voltage industrial controls and switchgear (EC000222)
Feature Name
Feature Value
Number of switch positions (EF000231)
2
Type of control element (EF006976)
Key
Suitable for lighting (EF001142)
No
Colour control element (EF007167)
Black
Colour indicator light cap (EF007165)
Other
Construction type lens (EF006253)
Round
Hole diameter (EF000079)
30 mm
Width opening (EF004565)
0 mm
Height opening (EF004778)
0 mm
Switching function latching (EF007447)
Yes
Spring-return (EF001407)
No
With front ring (EF006014)
Yes
Material front ring (EF005972)
Metal
Colour front ring (EF002429)
Chrome
Degree of protection (IP), front side (EF003118)
IP66
Degree of protection (NEMA) (EF011959)
4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWRS*-MS*-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.