

INDUSTRIAL COMPONENT DATA

M30C-FWRS-RS 187062 Y7-187062 EATON ELECTRIC

Key-operated actuators, Flat Front, not suitable for master key..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWRS-RS



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWRS-RS
Catalog number	Y7-187062
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-CEE46D29BA
Generated	2026-08-05

Product Overview

Key-operated actuators, Flat Front, not suitable for master key systems, 2 positions, maintained, Ronis 455
M30C-FWRS-RS

Eaton Moeller® series M30 Key-operated actuator, Flat Front, maintained, 2 positions, Ronis 455, Key withdrawable: 0, I, Metal bezel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, maintained, Not suitable for master key systems, 2 positions, Lock mechanism: Ronis 455, I, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 187062 Model Code M30C-FWRS-RS
EAN 4015081821259 Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg
Certifications VDE 0660
IEC/EN 60947

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Features & Functions

Bezel color Titanium Bezel material Metal Design Key operation lock mechanism

Flat front Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Key code Ronis 455 General

Accessories 2 keys included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side) IP64 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 100 Operations/h Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 60 ° Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cy...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWRS-RS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.