

INDUSTRIAL COMPONENT DATA

M30C-FWRS-SA(*)-*-A8 187066 Y7-187066 EATON ELECTRIC

Key-operated actuators, Flat Front, suitable for master..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWRS-SA(*)-*-A8



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWRS-SA(*)-*-A8
Catalog number	Y7-187066
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-DE844D064B
Generated	2026-08-04

Product Overview

Key-operated actuators, Flat Front, suitable for master key systems, 2 positions, maintained

M30C-FWRS-SA(*)-*-A8

Key-operated actuator, RMQ-Titan, key operation lock mechanism, maintained, Suitable for master key systems, 2 positions, I, Metal bezel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, maintained, Suitable for master key systems, 2 positions, I, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, RMQ-Titan, key operation lock mechanism, maintained, Suitable for master key systems, 2 positions, I, Metal bezel Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, maintained, Suitable for master key systems, 2 positions, I, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64 Delivery program

Product range RMQ-Titan Basic function Key-operated buttons Single unit/Complete unit Single unit Design key operation lock mechanism maintained Function: [= spring-return] 60° Suitable for master key systems 2 positions Key withdrawable in position 0 I Degree of Protection IP66 Front ring Metal bezel Connection to SmartWire-DT yes

with SWD-RMQ connections Front dimensions Ø 36 mm Information about equipment supplied with two keys Technical data

General Standards IEC/EN 60947

VDE 0660 Lifespan, mechanical [Operations] > 0.1 x 10⁶ Operating frequency [Operations/h] ? 100 Operating torque ? 0.5 Nm Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66 Ambient temperatureOpen -25 - +70 °C Mounting position

As required Mechanical shock resistance 15

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 g shipping classification DNV

GL Design verification as per IEC/EN 61439

Operating ambient temperat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWRS-SA(*)-*A8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.