

INDUSTRIAL COMPONENT DATA

M30C-FWRS3-SA(*)-* 187100 Y7-187100 EATON ELECTRIC

Key-operated actuators, Flat Front, suitable for master k..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWRS3-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWRS3-SA(*)-*
Catalog number	Y7-187100
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-4B02F6AF36
Generated	2026-08-04

Product Overview

Key-operated actuators, Flat Front, suitable for master key systems, 3 positions, maintained
M30C-FWRS3-SA(*)-*

Key-operated actuator, Flat Front, maintained, 3 positions 0, Metal bezel, Suitable for master key systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Key-operated actuator, Flat Front, maintained, 3 positions 0, Metal bezel, Suitable for master key systemsKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, maintained, Suitable for master key systems, 3 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64Delivery program

Product rangeFlat Front (drilling dimensions 30.5 mm)Basic functionKey-operated buttonsMounting hole diameter [?]30.5 mmSingle unit/Complete unitSingle unitDesignkey operation lock mechanismmaintainedFunction: [= spring-return]60° ? 60°Suitable for master key systems3 positionsKey withdrawable in position0Degree of ProtectionIP64Front ringMetal bezelConnection to SmartWire-DTyes

with SWD-RMQ connectionsInformation about equipment suppliedwith two keysTechnical data

GeneralStandardsIEC/EN 60947

VDE 0660Lifespan, mechanical [Operations]> 0.1 x 106Operating frequency [Operations/h]? 100Operating torque? 0.5 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP64 Ambient temperature Open-25 - +70 °C Mounting position As required
Mechanical shock resistance 15
Shock duration 11 ms
Sinusoidal
according to IEC 60068-2-27 g shipping classification DNV
GL Design verification as per IEC/EN 61439
Operating ambient temperature min. -25 °C Operating ambient temp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWRS3-SA(*)-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.