

INDUSTRIAL COMPONENT DATA

M30C-FWS 187068 Y7-187068 EATON ELECTRIC

Key-operated actuators, Flat Front, not suitable for master key sys..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWS



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWS
Catalog number	Y7-187068
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-F759783844
Generated	2026-08-04

Product Overview

Key-operated actuators, Flat Front, not suitable for master key systems, 2 positions, momentary
M30C-FWS

Eaton Moeller® series M30 Key-operated actuator, Flat Front, momentary, 2 positions, Key withdrawable: 0, Metal bezel
Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, momentary, Not suitable for master key systems, 2 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 187068 Model Code M30C-FWS EAN 4015081821297 Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg

Certifications VDE 0660

IEC/EN 60947 Features & Functions

Bezel color Titanium Bezel material Metal Design Key operation lock mechanism Fitted with: Front ring Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General
Accessories 1 key included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side)
IP66 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 100 Operations/h Operating
torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm
Switching angle 40 ° Type Key-operated button Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuator color Black Actuator function Key withdrawable in position 0
Spring-return
Momentary Actuator type Key Number of switch....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWS with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.