

## INDUSTRIAL COMPONENT DATA

# M30C-FWS-MS2 187073 Y7-187073 EATON ELECTRIC

## Key-operated actuators, Flat Front, not suitable for master key..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWS-MS2



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | M30C-FWS-MS2                      |
| Catalog number  | Y7-187073                         |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-E70177D790                     |
| Generated       | 2026-08-04                        |

## Product Overview

Key-operated actuators, Flat Front, not suitable for master key systems, 2 positions, momentary, MS2

M30C-FWS-MS2

Eaton Moeller® series M30 Key-operated actuator, Flat Front, momentary, 2 positions, MS2, Key withdrawable: 0, Metal bezel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, momentary, Not suitable for master key systems, 2 positions, Lock mechanism: MS2, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 187073 Model Code M30C-FWS-MS2

EAN 4015081821327 Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg

Certifications IEC/EN 60947

VDE 0660

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Features & Functions

Bezel color Titanium Bezel material Metal Design Key operation lock mechanism

Flat front Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Key code MS2 General

Accessories 1 key included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 100 Operations/h Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 40 ° Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWS-MS2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.