

INDUSTRIAL COMPONENT DATA

M30C-FWS-SA(*)-* 187076 Y7-187076 EATON ELECTRIC

Key-operated actuators, Flat Front, suitable for master key..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWS-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWS-SA(*)-*
Catalog number	Y7-187076
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-DC0B86D795
Generated	2026-08-04

Product Overview

Key-operated actuators, Flat Front, suitable for master key systems, 2 positions, momentary
M30C-FWS-SA(*)-*

Key-operated actuator, Flat Front, momentary, 2 positions 0, Metal bezel, Suitable for master key systems

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, momentary, Suitable for master key systems, 2 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, Flat Front, momentary, 2 positions 0, Metal bezel, Suitable for master key systemsKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, momentary, Suitable for master key systems, 2 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64
General specificationsProduct nameEaton Moeller® series M30 Key-operated actuatorPart no.M30C-FWS-SA(*)-*Product Length/Depth36 millimetreProduct height75 millimetreProduct width46 millimetreProduct weight0.085 kilogramCertificationsVDE 0660

IEC/EN 60947Product TradenameM30Product TypeKey-operated actuatorProduct Sub TypeNoneFeatures & FunctionsBezel colorTitaniumBezel materialMetalDesignKey operation lock mechanismFitted with:Front ringGeneral

informationAccessories2 keys included with supplied equipment.Degree of protectionNEMA 4X, 13Degree of protection (front side)IP66Lifespan, mechanical100,000 OperationsOpening diameter30 mmOperating frequency100 Operations/hOperating torque0.5 N·mProduct categoryRMQ-TitanSizeFront dimensions: Ø 36 mmSuitable forMaster key systemsSwitching angle40 °TypeKey-operated buttonAmbient conditions, mechanicalMounting positionAs requiredShock resistance15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27Climatic environmental...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWS-SA(*)-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.