

INDUSTRIAL COMPONENT DATA

M30C-FWS3-SA(*)-* 187071 Y7-187071 EATON ELECTRIC

Key-operated actuators, Flat Front, suitable for master ke..

Brand: EATON - MOELLER | Manufacturer Part Number: M30C-FWS3-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30C-FWS3-SA(*)-*
Catalog number	Y7-187071
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-2E2704F7EE
Generated	2026-08-03

Product Overview

Key-operated actuators, Flat Front, suitable for master key systems, 3 positions, momentary

M30C-FWS3-SA(*)-*

Key-operated actuator, Flat Front, momentary, 3 positions 0, Metal bezel, Suitable for master key systems

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: key operation lock mechanism, momentary, Suitable for master key systems, 3 positions, Degree of Protection: IP64, Metal bezel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 187071 Model Code

M30C-FWS3-SA(*)-* Product Length/Depth 36 mm Product Height 75 mm Product Width 46 mm Product Weight 0.085 kg

Certifications IEC/EN 60947

VDE 0660

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified Features & Functions
Bezel color Titanium Bezel material Metal Design Key operation lock mechanism
Flat front Fitted with: Front ring General
Accessories 2 keys included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side)
IP64 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 100 Operations/h Operating
torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm
Suitable for Master key systems Switching angle 40 ° Type Key-operated button Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30C-FWS3-SA(*)-* with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.