

INDUSTRIAL COMPONENT DATA

M30I-FD-R-X0 188105 Y7-188105 EATON ELECTRIC

Push-buttons, flat front, flush, momentary, red, labeled

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FD-R-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FD-R-X0
Catalog number	Y7-188105
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-0FB294B3F1
Generated	2026-08-03

Product Overview

Push-buttons, flat front, flush, momentary, red, labeled

M30I-FD-R-X0

Eaton Moeller® series M30 Pushbutton, RMQ-Titan, flat, momentary, red, inscribed, Front ring stainless steel Pushbutton, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: red, Button plate inscribed, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 x 3mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Pushbutton Catalog Number 188105 Model Code M30I-FD-R-X0 EAN 4015081857838 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg

Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05 and 94-M91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Product specifications

Type Pushbutton actuator Actuator color Red Features Labelled Actuator function Spring-return

Momentary Fitted with: Front ring Operating frequency 3600 Operations/h Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuating force 5 N Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Ambient storage temperature - max 80 °C Ambient storage temperature - min 40 °C Force for positive opening - min 0 N Number of command positions 1 Opening diameter 30.5 mm Opening height 0 mm Bezel color Stainless steel Shock resistance

Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Bezel material Metal Design Flat

Flat front Mounting position As required Degree of protection IP67

IP66

IP69 Degree of protection (front side) IP67

NEMA 4X, 13 Inscription Inscribed Front element type Flat Lens type Round Lifespan, mechanical 5,0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FD-R-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.