

INDUSTRIAL COMPONENT DATA

M30I-FD-W-X1 188055 Y7-188055 EATON ELECTRIC

Push-buttons, flat front, flush, momentary, white, labeled

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FD-W-X1



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FD-W-X1
Catalog number	Y7-188055
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-7C7EA76305
Generated	2026-08-04

Product Overview

Push-buttons, flat front, flush, momentary, white, labeled

M30I-FD-W-X1

Pushbutton, RMQ-Titan, flat, momentary, White, inscribed 1, Front ring stainless steel

Pushbutton, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: White, Button plate inscribed, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 x 3mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Pushbutton, RMQ-Titan, flat, momentary, White, inscribed 1, Front ring stainless steelPushbutton, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: White, Button plate inscribed, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 x 3mm, Standards: IEC/EN 60947, VDE 0660

General specificationsProduct nameEaton Moeller® series M30 PushbuttonPart

no.M30I-FD-W-X1EAN4015081857340Product Length/Depth36 millimetreProduct height30 millimetreProduct width46 millimetreProduct weight0.041 kilogramCertificationsVDE 0660

IEC/EN 60947

IEC/EN 60947-5

CSA File No.: 012528

CSA certified

UL File No.: E29184

UL Category Control No.: NKCR

UL Listed

DNV

CSA Class No.: 3211-03

GL

UL 508

CE marking

CSA-C22.2 No. 14-05 and 94-M91Product TradenameM30Product TypePushbuttonProduct Sub TypeNoneFeatures &

FunctionsBezel colorStainless steelBezel materialMetalDesignFlat

Flat frontFeaturesLabelledFitted with:Front ringInscriptionInscribedGeneral informationDegree of protectionIP66

IP67

IP69Degree of protection (front side)IP67

NEMA 4X, 13Lifespan, mechanical5,000,000 OperationsOpening diameter30.5 mmOperating frequency3600

Operations/hProduct categoryRMQ-TitanSizeFront dimensions: Ø 36 x 3 mmTypePushbutton actuatorAmbient conditions,

mechanicalMounting positionAs requiredShock resistance15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal

shock 11 ms

Mechanical, According....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FD-W-X1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.