

INDUSTRIAL COMPONENT DATA

M30I-FDL-B-SP 197014 Y7-197014 EATON ELECTRIC

Illuminated push-button actuators, flat front, flush, momentar..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDL-B-SP



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDL-B-SP
Catalog number	Y7-197014
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-52B8974ECD
Generated	2026-08-01

Product Overview

Illuminated push-button actuators, flat front, flush, momentary, blue, blank

M30I-FDL-B-SP

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, Blue, blank, Front ring stainless steel M30I-FDL-B-SP

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: flat, momentary, Description: Sealed and undetachable pushbutton pressel, button plate: Blue, Button plate blank, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 197014 Model Code

M30I-FDL-B-SP EAN 4015080892755 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg Certifications VDE 0660

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05 and 94-M91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Catalog Notes Sealed and undetachable pushbutton pressel

ETIM for 197014 Low-voltage industrial controls and switchgear (EC000221)

Feature Name

Feature Value

Colour button (EF000190)

Blue

Number of command positions (EF001372)

1

Construction type lens (EF006253)

Round

Hole diameter (EF000079)

30.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Type of button (EF001546)

Flat

Suitable for lighting (EF001142)

Yes

With protective cover (EF005500)

No

Labelled (EF001537)

No

Switching function latching (EF007447)

No

Spring-return (EF001407)

Yes

With front ring (EF006014)

Yes

Material front ring (EF005972)

Metal

Colour front ring (EF002429)

Stainless steel

Degree of protection (IP), front side (EF003118)

IP67

Degree of protection (NEMA), front side (EF011961)

4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDL-B-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.