

INDUSTRIAL COMPONENT DATA

M30I-FDL-G 188060 Y7-188060 EATON ELECTRIC Illuminated push-button actuators, flat front, flush, momentary, ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDL-G



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDL-G
Catalog number	Y7-188060
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-7AA2F3661A
Generated	2026-08-04

Product Overview

Illuminated push-button actuators, flat front, flush, momentary, green, blank

M30I-FDL-G

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, green, blank, Front ring stainless steel M30I-FDL-G

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: green, Button plate blank, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 188060 Model Code M30I-FDL-G EAN 4015081857395 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified
ETIM for 188060 Low-voltage industrial controls and switchgear (EC000221)
Feature Name
Feature Value
Colour button (EF000190)
Green
Number of command positions (EF001372)
1
Construction type lens (EF006253)
Round
Hole diameter (EF000079)
30.5 mm
Width opening (EF004565)
0 mm
Height opening (EF004778)
0 mm
Type of button (EF001546)
Flat
Suitable for lighting (EF001142)
Yes
With protective cover (EF005500)
No
Labelled (EF001537)
No
Switching function latching (EF007447)
No
Spring-return (EF001407)
Yes
With front ring (EF006014)
Yes
Material front ring (EF005972)
Metal
Colour front ring (EF002429)
Stainless steel
Degree of protection (IP), front side (EF003118)
IP67
Degree of protection (NEMA), front side (EF011961)
4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDL-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.