

INDUSTRIAL COMPONENT DATA

M30I-FDL-W-X100 188041 Y7-188041 EATON ELECTRIC

Illuminated push-buttons, flat front, flush, momentary, whit..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDL-W-X100



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDL-W-X100
Catalog number	Y7-188041
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-277FD2E7CC
Generated	2026-08-03

Product Overview

Illuminated push-buttons, flat front, flush, momentary, white, labeled

M30I-FDL-W-X100

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, White, inscribed, Front ring stainless steel

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: White, Button plate inscribed, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 188041 Model Code M30I-FDL-W-X100 EAN 4015081857265 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified Features & Functions
Bezel color Stainless steel Bezel material Metal Design Flat
Flat front Features Labelled Fitted with: Front ring Inscription Inscribed General
Degree of protection IP67
IP66
IP69 Degree of protection (front side) IP67
NEMA 4X, 13 Lifespan, mechanical 5,000,000 Operations Opening diameter 30.5 mm Operating frequency 3600
Operations/h Product category RMQ-Titan Size Front dimensions: Ø 36 mm Suitable for Illumination Type Illuminated
pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT With SWD-RMQ connections
Yes Actuator
Actuating force 5 N Actuator color White Actuator functi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDL-W-X100 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.