

INDUSTRIAL COMPONENT DATA

M30I-FDL-Y-X162 188040 Y7-188040 EATON ELECTRIC Illuminated push-buttons, flat front, flush, momentary, yell..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDL-Y-X162



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDL-Y-X162
Catalog number	Y7-188040
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-062313341F
Generated	2026-08-05

Product Overview

Illuminated push-buttons, flat front, flush, momentary, yellow, labeled

M30I-FDL-Y-X162

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, yellow, inscribed, Front ring stainless steel

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: flat, momentary, button plate: yellow, Button plate inscribed, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 188040 Model Code M30I-FDL-Y-X162 EAN 4015081857258 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified
ETIM for 188040 Low-voltage industrial controls and switchgear (EC000221)
Feature Name
Feature Value
Colour button (EF000190)
Yellow
Number of command positions (EF001372)
1
Construction type lens (EF006253)
Round
Hole diameter (EF000079)
30.5 mm
Width opening (EF004565)
0 mm
Height opening (EF004778)
0 mm
Type of button (EF001546)
Flat
Suitable for lighting (EF001142)
Yes
With protective cover (EF005500)
No
Labelled (EF001537)
Yes
Switching function latching (EF007447)
No
Spring-return (EF001407)
Yes
With front ring (EF006014)
Yes
Material front ring (EF005972)
Metal
Colour front ring (EF002429)
Stainless steel
Degree of protection (IP), front side (EF003118)
IP67
Degree of protection (NEMA), front side (EF011961)
4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDL-Y-X162 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.