

INDUSTRIAL COMPONENT DATA

M30I-FDR-S 188092 Y7-188092 EATON ELECTRIC

Push-buttons, flat front, flush, maintained, black, blank

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDR-S



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDR-S
Catalog number	Y7-188092
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-5157D65E07
Generated	2026-08-02

Product Overview

Push-buttons, flat front, flush, maintained, black, blank

M30I-FDR-S

Eaton Moeller® series M30 Pushbutton, RMQ-Titan, flat, maintained, black, blank, Front ring stainless steel

Pushbutton, Product range: RMQ-Titan, Single unit, Design: flat, maintained, button plate: black, Button plate blank, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36 x 3mm, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Pushbutton Catalog Number 188092 Model Code M30I-FDR-S EAN

4015081857708 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg

Certifications VDE 0660

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL
IEC/EN 60947-5
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CE marking
UL Category Control No.: NKCR
UL Listed
CSA certified Features & Functions
Bezel color Stainless steel Bezel material Metal Design Flat
Flat front Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank
General
Degree of protection IP66
IP67
IP69 Degree of protection (front side) IP67
NEMA 4X, 13 Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 30.5 mm Operating frequency 1800 Operations/h Product category RMQ-Titan Size Front dimensions: Ø 36 x 3 mm Type Pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT Yes
With SWD-RM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDR-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.