

## INDUSTRIAL COMPONENT DATA

# M30I-FDR-W 188093 Y7-188093 EATON ELECTRIC

## Push-buttons, flat front, flush, maintained, white, blank

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDR-W



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M30I-FDR-W                    |
| Catalog number  | Y7-188093                     |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-4A574720B8                 |
| Generated       | 2026-08-04                    |

### Product Overview

Push-buttons, flat front, flush, maintained, white, blank

M30I-FDR-W

Eaton Moeller® series M30 Pushbutton, RMQ-Titan, flat, maintained, White, blank, Front ring stainless steel  
Pushbutton, Product range: RMQ-Titan, Single unit, Design: flat, maintained, button plate: White, Button plate blank,  
Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ  
connections, Front dimensions: Ø 36 x 3mm, Instructions: Stay-put/spring-return function can be changed on device,  
Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Pushbutton Catalog Number 188093 Model Code M30I-FDR-W EAN  
4015081857715 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product Weight 0.041 kg  
Certifications IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL  
IEC/EN 60947-5  
UL 508  
CSA-C22.2 No. 14-05 and 94-M91  
CE marking  
UL Category Control No.: NKCR  
UL Listed  
CSA certified Features & Functions  
Bezel color Stainless steel Bezel material Metal Design Flat  
Flat front Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank  
General  
Degree of protection IP67  
IP69  
IP66 Degree of protection (front side) IP67  
NEMA 4X, 13 Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 30.5 mm Operating frequency 1800 Operations/h Product category RMQ-Titan Size Front dimensions: Ø 36 x 3 mm Type Pushbutton actuator Ambient conditions, mechanical  
Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms  
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions  
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30  
Damp heat, constant, to IEC 60068-2-78 Communication  
Connection to SmartWire-DT Yes  
With SWD-RM...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDR-W with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.