

INDUSTRIAL COMPONENT DATA

M30I-FDRL-G 188027 Y7-188027 EATON ELECTRIC

Illuminated push-buttons, flat front, flush, maintained, green,

..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FDRL-G



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FDRL-G
Catalog number	Y7-188027
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-A21FC4EF57
Generated	2026-08-03

Product Overview

Illuminated push-buttons, flat front, flush, maintained, green, blank

M30I-FDRL-G

Eaton Moeller® series M30 Illuminated pushbutton actuator, RMQ-Titan, flat, maintained, green, blank, Front ring stainless steel

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: flat, maintained, button plate: green, Button plate blank, Degree of Protection: IP66, IP67, IP69, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated pushbutton actuator Catalog Number 188027 Model Code

M30I-FDRL-G EAN 4015081857128 Product Length/Depth 36 mm Product Height 30 mm Product Width 46 mm Product

Weight 0.041 kg Certifications VDE 0660

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05 and 94-M91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified

ETIM for 188027 Low-voltage industrial controls and switchgear (EC000221)

Feature Name

Feature Value

Colour button (EF000190)

Green

Number of command positions (EF001372)

1

Construction type lens (EF006253)

Round

Hole diameter (EF000079)

30.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Type of button (EF001546)

Flat

Suitable for lighting (EF001142)

Yes

With protective cover (EF005500)

No

Labelled (EF001537)

No

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No

With front ring (EF006014)

Yes

Material front ring (EF005972)

Metal

Colour front ring (EF002429)

Stainless steel

Degree of protection (IP), front side (EF003118)

IP67

Degree of protection (NEMA), front side (EF011961)

4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FDRL-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.