

INDUSTRIAL COMPONENT DATA

M30I-FL-B-* 188051 Y7-188051 EATON ELECTRIC Indicator light, flat front, flush, blue, individual facility fo..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FL-B-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FL-B-*
Catalog number	Y7-188051
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-A445659108
Generated	2026-08-01

Product Overview

Indicator light, flat front, flush, blue, individual facility for inscription
M30I-FL-B-*

Eaton Moeller® series M30 Indicator light, RMQ-Titan, flat, Blue, individual facility for inscription, Front ring stainless steel
Indicator light, Product range: RMQ-Titan, Single unit, Design: flat, Color Lens: Blue, Button plate individual facility for inscription, Degree of Protection: IP66, IP67, IP69K, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Indicator light Catalog Number 188051 Model Code M30I-FL-B-* Product Length/Depth 36 mm Product Height 32 mm Product Width 46 mm Product Weight 0.035 kg Certifications IEC/EN 60947 VDE 0660 Features & Functions
Bezel color Chrome Bezel material Metal Design Flat Fitted with: Front ring Inscription Individual inscription possible Lens color Blue General
Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 30 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front dimensions: Ø 36 mm Type Indicator lights Ambient conditions, mechanical
Mounting position As required Shock resistance Not planned Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Contacts

Force for positive opening - min 0 N

ETIM for 188051 Low-voltage industrial controls and switchgear (EC000223)

Feature Name

Feature Value

Suitable for number of built-in signal lights (EF006669)

1

Colour lens (EF000207)

Blue

Construction type lens (EF006253)

Round

Hole diameter (EF000079)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FL-B-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.