

INDUSTRIAL COMPONENT DATA

M30I-FR-SWD 188127 Y7-188127 EATON ELECTRIC Potentiometer, flat front, SWD-ready, front mounting

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FR-SWD



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FR-SWD
Catalog number	Y7-188127
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-959DCE18E9
Generated	2026-08-04

Product Overview

Potentiometer, flat front, SWD-ready, front mounting

M30I-FR-SWD

Eaton Moeller® series M30 Potentiometer, flat front, M30, 30.5 mm, Front ring stainless steel

Potentiometer, Subrange: SmartWire-DT RMQ connections, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: Front element SmartWire-DT potentiometer, Only in conjunction with M22-SWD-R function element, Function: For connecting to SmartWire-DT, Degree of Protection: IP65, Front ring stainless steel, Connection to SmartWire-DT: yes, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Potentiometer Catalog Number 188127 Model Code M30I-FR-SWD EAN 4015081858057 Product Length/Depth 36 mm Product Height 48 mm Product Width 46 mm Product Weight 0.05 kg

Certifications IEC/EN 60947 Product specifications

Type Potentiometer Electric connection type Screw connection Climatic proofing Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Connection to SmartWire-DT Yes Bezel color Stainless steel Ambient operating temperature - max 70 °C Ambient operating temperature - min -30 °C Ambient storage temperature - max 70 °C Ambient storage temperature - min -40 °C Number of revolutions - max 1 Number of revolutions - min 1 Opening diameter 30 mm Design Flat front Mounting position As required Degree of protection IP65

NEMA Other Functions For connecting to SmartWire-DT Power consumption 0 W Resistance 0 Ohm

ETIM for 188127 Low-voltage industrial controls and switchgear (EC001027)

Feature Name

Feature Value

Resistance (EF002431)

0 Ohm

Power consumption (EF000346)

0 W

Hole diameter (EF000079)

30 mm

Number of revolutions (EF006943)

1

Type of electric connection (EF003961)

Screw connection

Degree of protection (IP) (EF005474)

IP65

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FR-SWD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.