

INDUSTRIAL COMPONENT DATA

M30I-FR1K-BLANK 188117 Y7-188117 EATON ELECTRIC Potentiometer, flat front, without scale/inscription, R 1 kΩ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FR1K-BLANK



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FR1K-BLANK
Catalog number	Y7-188117
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-3B047E2089
Generated	2026-08-04

Product Overview

Potentiometer, flat front, without scale/inscription, R = 1 kΩ

M30I-FR1K-BLANK

Potentiometer, flat front, M30, 30.5 mm, Without scale/inscription, R 1 kΩ, P 0.5 W, Front ring stainless steel

Potentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit,

Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Without scale/inscription,

Impedance: R= 1 kΩ, Rated power: P= 0.5 W, Degree of Protection: IP66, Front ring stainless steel, Connection to

SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Potentiometer, flat front, M30, 30.5 mm, Without scale/inscription, R 1 kΩ, P 0.5 W, Front ring stainless steel
Potentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Without scale/inscription, Impedance: R= 1 kΩ, Rated power: P= 0.5 W, Degree of Protection: IP66, Front ring stainless steel, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

General specificationsProduct nameEaton Moeller® series M30 PotentiometerPart

no.M30I-FR1K-BLANKEAN4015081857951Product Length/Depth36 millimetreProduct height63 millimetreProduct width46 millimetreProduct weight0.055 kilogramCertificationsIEC/EN 60947

VDE 0660Product TradenameM30Product TypePotentiometerProduct Sub TypeNoneCatalog NotesWithout

scale/inscriptionFeatures & FunctionsBezel colorStainless steelDesignFlat frontElectric connection typeScrew connectionFitted with:3 individual screw terminalsGeneral informationAccuracy $\pm 10\%$ (linear), Resistance valueDegree of protectionIP66
NEMA OtherLifespan, mechanical25,000 OperationsOpening diameter30 mmOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)4000 V ACTypePotentiometerAmbient conditions, mechanicalMounting positionAs requiredShock resistanceNot plannedClimatic environmental conditionsAmbient operating temperature - min-25 °C
Ambient operating temperature - max70 °CClimatic proofingDamp....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FR1K-BLANK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.