

INDUSTRIAL COMPONENT DATA

M30I-FR47K-BLANK 188122 Y7-188122 EATON ELECTRIC Potentiometer, flat front, without scale/inscription, R 47 ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FR47K-BLANK



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FR47K-BLANK
Catalog number	Y7-188122
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-06EAD9C9B9
Generated	2026-08-05

Product Overview

Potentiometer, flat front, without scale/inscription, R = 47 kOhm

M30I-FR47K-BLANK

Eaton Moeller® series M30 Potentiometer, flat front, M30, 30.5 mm, Without scale/inscription, R 47 k?, P 0.5 W, Front ring stainless steel

Potentiometer, RMQ design: flat front, Part group reference (e.g. DIL): M30, Mounting hole diameter: 30.5 mm, Single unit, Description: 3 individual screw terminals, Accuracy of resistance value: $\pm 10\%$ (linear), Without scale/inscription, Impedance: R= 47 k?, Rated power: P= 0.5 W, Degree of Protection: IP66, Front ring stainless steel, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Potentiometer Catalog Number 188122 Model Code M30I-FR47K-BLANK EAN 4015081858002 Product Length/Depth 36 mm Product Height 63 mm Product Width 46 mm Product Weight 0.055 kg

Certifications IEC/EN 60947

VDE 0660 Catalog Notes Without scale/inscription Features & Functions

Bezel color Stainless steel Design Flat front Electric connection type Screw connection Fitted with: 3 individual screw terminals General

Accuracy $\pm 10\%$ (linear), Resistance value Degree of protection IP66

NEMA Other Lifespan, mechanical 25,000 Operations Opening diameter 30 mm Overvoltage category III Pollution degree 3
Rated impulse withstand voltage (Uimp) 4000 V AC Type Potentiometer Ambient conditions, mechanical
Mounting position As required Shock resistance Not planned Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Terminal capacities
Terminal capacity (solid) 0.5 - 1.5 mm² Terminal capacity (stranded) 0.5 - 1.5 mm² Tightening torque 0.5 Nm, Screw
terminals Electrical rating
Power consumption 0.5 W Rated insulation voltage (Ui) 250 V Rated power 0.5 VA Resistance 47000 Ohm Communication
Connection to SmartWire-DT No
ETIM for 188122 Low-voltage industrial controls and switchgear (EC001027)
Feature Name
Feature Value
Resistance (EF002431)
47000 Ohm
Power consumption (EF000346)
0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FR47K-BLANK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.