

INDUSTRIAL COMPONENT DATA

M30I-FUSB-150 188132 EATON ELECTRIC Fuse-link, low voltage, 150 A, AC 300 V, DC 160 V, 61.9 x 22.2, T, UL, v..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FUSB-150



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FUSB-150
Catalog number	188132
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-A8CEB75FEE
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 150 A, AC 300 V, DC 160 V, 61.9 x 22.2, T, UL, very fast acting

USB 3.0 interface; 30 mm; Female, cable 1.5 m; Ring Stainless Flat Front

Bulkhead interface, 1.5 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Front ring stainless steel

Bulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable

length: 1.5 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Front ring stainless steel,

Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Bulkhead interface, 1.5 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Front ring stainless

steelBulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable

length: 1.5 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Front ring stainless steel,

Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9Delivery program

AccessoriesGeneral accessoriesBasic function accessoriesBulkhead interface, RJ45 socketPrefabricated cable with

permanently connected USB 3.0 Type A plugCable length1.5 mDegree of ProtectionIP65 (with closed cover)

IP20 (with plug connected)Front ringFront ring stainless steelConnection to SmartWire-DTnoFor use withFront

mountingTerminal diagram / contact assignmentTechnical data

Technical dataNominal voltage [UL]AC/DC 5VVoltage rangeMax. 30 VNumber of poles9Class / category3.0Screen earth

kitiesGeneralDesignUSB 3.0 AInsulation resistance [RISO]> ? 100 M?Mounting depth:ca. 70 (incl. Krümmung) mmOuter

cable diameter6.1 mmTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)Type of electrical
accessoryOtherType of mechanical accessoryOtherCharacteristics

Terminal diagram / contact assignment

ETIM for 188132 Low-voltage industrial controls and switchgear (EC002024)

Feature Name

Feature Value

Accessory (EF013236)

No

Spare part (EF013237)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FUSB-150 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.