

INDUSTRIAL COMPONENT DATA

M30I-FUSB-30 188130 EATON ELECTRIC Fuse-link, LV, 30 A, AC 600 V, 21 x 57 mm, J, UL, fast acting

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FUSB-30



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FUSB-30
Catalog number	188130
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-96E758F3A0
Generated	2026-08-06

Product Overview

Fuse-link, LV, 30 A, AC 600 V, 21 x 57 mm, J, UL, fast acting

USB 3.0 interface; 30 mm; Female/cable 30 cm; Ring Stainless Flat Front

Bulkhead interface, 0.3 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Front ring stainless steel

Bulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable

length: 0.3 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Front ring stainless steel,

Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Bulkhead interface, 0.3 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Front ring stainless

steelBulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable

length: 0.3 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Front ring stainless steel,

Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9Delivery program

AccessoriesGeneral accessoriesBasic function accessoriesBulkhead interface, RJ45 socketPrefabricated cable with

permanently connected USB 3.0 Type A plugCable length0.3 mDegree of ProtectionIP65 (with closed cover)

IP20 (with plug connected)Front ringFront ring stainless steelConnection to SmartWire-DTnoFor use withFront

mountingTerminal diagram / contact assignmentTechnical data

Technical dataNominal voltage [UL]AC/DC 5VVoltage rangeMax. 30 VNumber of poles9Class / category3.0Screen earth

kitiesGeneralDesignUSB 3.0 AInsulation resistance [RISO]> ? 100 M?Mounting depth:ca. 70 (incl. Krümmung) mmOuter

cable diameter6.1 mmTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)Type of electrical

accessoryOtherType of mechanical accessoryOtherCharacteristics

Terminal diagram / contact assignment

ETIM for 188130 Low-voltage industrial controls and switchgear (EC002024)

Feature Name

Feature Value

Accessory (EF013236)

No

Spare part (EF013237)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FUSB-30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.