

INDUSTRIAL COMPONENT DATA

M30I-FW 188134 Y7-188134 EATON ELECTRIC Selector switch actuators, flat front, with control knob, labeled, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FW



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FW
Catalog number	Y7-188134
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-8FCE67463B
Generated	2026-08-02

Product Overview

Selector switch actuators, flat front, with control knob, labeled, 2 positions, momentary

M30I-FW

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, with rotary head, momentary, 2 positions, inscribed, Front ring stainless steel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: with rotary head, momentary, 2 positions, inscribed, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 188134 Model Code M30I-FW EAN 4015081858118 Product Length/Depth 36 mm Product Height 43 mm Product Width 46 mm Product Weight 0.042 kg Certifications IEC/EN 60947

VDE 0660 Features & Functions

Bezel color Stainless steel Bezel material Metal Design With rotary head Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Inscription Inscribed General Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations

Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III
Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 40 ° Type Selector switch
actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min
40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuator color Black Actuator function Spring-return
Momentary Actuator type Turn bu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FW with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.