

## INDUSTRIAL COMPONENT DATA

# M30I-FW3 188136 Y7-188136 EATON ELECTRIC Selector switch actuators, flat front, with control knob, labeled, ..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FW3



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | M30I-FW3                          |
| Catalog number  | Y7-188136                         |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-5A3685998F                     |
| Generated       | 2026-08-02                        |

## Product Overview

Selector switch actuators, flat front, with control knob, labeled, 3 positions, momentary

M30I-FW3

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, with rotary head, momentary, 3 positions, inscribed, Front ring stainless steel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: with rotary head, momentary, 3 positions, inscribed, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, with plunger bridge for the middle contact, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 188136 Model Code M30I-FW3 EAN 4015081858132 Product Length/Depth 36 mm Product Height 43 mm Product Width 46 mm Product Weight 0.042 kg Certifications VDE 0660

IEC/EN 60947 Features & Functions

Bezel color Stainless steel Bezel material Metal Design With rotary head Fitted with: Plunger bridge for the middle contact Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Inscription Inscribed General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations  
Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III  
Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 40 ° Type Selector switch  
actuator Ambient conditions, mechanical  
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27  
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions  
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min  
40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30 Communication  
Connection to SmartWire-DT Yes  
With SWD-RMQ connections Actuator  
Actuator color Black Actuator function Moment...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FW3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.