

INDUSTRIAL COMPONENT DATA

M30I-FWJS4 188178 Y7-188178 EATON ELECTRIC Joystick, flat front, momentary, vertical

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWJS4



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWJS4
Catalog number	Y7-188178
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-425827DEA4
Generated	2026-08-04

Product Overview

Joystick, flat front, momentary, vertical
M30I-FWJS4

Eaton Moeller® series M30 Joystick, RMQ-Titan, with metal shaft, 4 positions, Front ring stainless steel
Joystick, Product range: RMQ-Titan, Single unit, Description: with one operating point per operating direction, with metal shaft, 4 positions, Degree of Protection: IP66, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Function: momentary, in every position, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Joystick Catalog Number 188178 Model Code M30I-FWJS4 EAN 4015081858415 Product Length/Depth 36 mm Product Height 93 mm Product Width 46 mm Product Weight 0.06 kg
Certifications VDE 0660

IEC/EN 60947 Features & Functions

Bezel color Stainless steel Bezel material Metal Fitted with: Filament bulb (24 V)

Front ring

Metal shaft

Retraction in 0-position General

Degree of protection IP66

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 2000 Operations/h
Product Category RMQ-Titan Size Front dimensions: Ø 36 mm Type Joystick Ambient conditions, mechanical
Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Electrical rating

Rated operational current (Ie) at AC-21, 400 V, 415 V 0 A Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuating force 5 N Actuator function In every position

Momentary Number of actuation directions 4 Contacts

Force for positive opening - min 0 N

ETIM for 188178 Low-voltage industrial controls and switchgear (EC000632)

Feature Name

Feature Value

Rated operation current Ie at AC-21, 400 V (EF002417)

0 A

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWJS4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.