

INDUSTRIAL COMPONENT DATA

M30I-FWLK-R 188199 Y7-188199 EATON ELECTRIC

Illuminated option keys, flat front, with T-handle, red, 2 posit..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWLK-R



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWLK-R
Catalog number	Y7-188199
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-8096B47C55
Generated	2026-08-06

Product Overview

Illuminated option keys, flat front, with T-handle, red, 2 positions, momentary

M30I-FWLK-R

Eaton Moeller® series M30 Illuminated selector switch actuator, RMQ-Titan, with thumb-grip, momentary, 2 positions, red, Front ring stainless steel

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: with thumb-grip, momentary, 2 positions, Color Thumb-grip: red, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated selector switch actuator Catalog Number 188199 Model Code M30I-FWLK-R EAN 4015081858590 Product Length/Depth 36 mm Product Height 47 mm Product Width 46 mm Product Weight 0.042 kg Certifications IEC/EN 60947

VDE 0660

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Product specifications

Type Illuminated selector switch actuator Actuator color Red Actuator function Momentary

Spring-return Fitted with: Front ring Operating frequency 2000 Operations/h Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator type Toggle Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Force for positive opening - min 0 N Opening diameter 30 mm Opening height 0 mm Operating torque 0.3 Nm Switching angle 40 °

Width opening 0 mm Bezel color Stainless steel Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Bezel material Metal Design With thumb-grip

Flat front Mounting position As required Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Indicator color Red....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWLK-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.