

INDUSTRIAL COMPONENT DATA

M30I-FWLKV-Y 188068 Y7-188068 EATON ELECTRIC

Illuminated option keys, flat front, with T-handle, yellow, 2 p..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWLKV-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWLKV-Y
Catalog number	Y7-188068
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-505691D9D8
Generated	2026-08-05

Product Overview

Illuminated option keys, flat front, with T-handle, yellow, 2 positions (V position), maintained
M30I-FWLKV-Y

Eaton Moeller® series M30 Illuminated selector switch actuator, RMQ-Titan, with thumb-grip, maintained, 2 positions (V position), yellow, Front ring stainless steel

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: with thumb-grip, maintained, 2 positions (V position), Color Thumb-grip: yellow, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Illuminated selector switch actuator Catalog Number 188068 Model Code M30I-FWLKV-Y EAN 4015081857470 Product Length/Depth 36 mm Product Height 47 mm Product Width 46 mm Product Weight 0.042 kg Certifications VDE 0660

IEC/EN 60947 Features & Functions

Bezel color Stainless steel Bezel material Metal Design With thumb-grip Fitted with: Front ring Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations

Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III
Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Suitable for Illumination Switching angle
60 ° Type Illuminated selector switch actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuator color Yellow Actuator function Spring-return
Maintained Actuator type Toggle Number of switch positions 2 Contacts...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWLKV-Y with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.