

INDUSTRIAL COMPONENT DATA

M30I-FWR3-* 188183 Y7-188183 EATON ELECTRIC Selector switch actuators, flat front, with control knob, indivi..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWR3-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWR3-*
Catalog number	Y7-188183
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-D0D09D8EA5
Generated	2026-08-03

Product Overview

Selector switch actuators, flat front, with control knob, individual facility for inscription, 3 positions, maintained M30I-FWR3-*

Eaton Moeller® series M30 Changeover switch, RMQ-Titan, with rotary head, maintained, 3 positions, individual facility for inscription, Front ring stainless steel

Changeover switch, Product range: RMQ-Titan, Single unit, Design: with rotary head, maintained, 3 positions, individual facility for inscription, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, with plunger bridge for the middle contact, Notes on customized inscription -> Data sheet, additional product information (links), Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Selector switch Catalog Number 188183 Model Code M30I-FWR3-* Product Length/Depth 36 mm Product Height 43 mm Product Width 46 mm Product Weight 0.042 kg Certifications IEC/EN 60947 VDE 0660

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified Catalog Notes Notes on customized inscription -> Data sheet, additional product information (links) Features & Functions

Bezel color Stainless steel Bezel material Metal Design With rotary head

Flat front Fitted with: Front ring

Plunger bridge for the middle contact Functions Stay-put/spring-return function, can be changed with coding parts

M22-XC-Y Inscription Individual inscription possible General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations

Opening diameter 30 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III

Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 60 ° Type Selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperatur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWR3-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.