

INDUSTRIAL COMPONENT DATA

M30I-FWRJS2V 188083 Y7-188083 EATON ELECTRIC Joystick, flat front, maintained, vertical, metal shaft

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWRJS2V



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWRJS2V
Catalog number	Y7-188083
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-55456503B9
Generated	2026-08-04

Product Overview

Joystick, flat front, maintained, vertical, metal shaft

M30I-FWRJS2V

Eaton Moeller® series M30 Joystick, RMQ-Titan, vertically momentary, with metal shaft, 2 positions, Front ring stainless steel

Joystick, Product range: RMQ-Titan, Single unit, Description: with one operating point per operating direction, with metal shaft, 2 positions, Degree of Protection: IP66, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Function: maintained, Vertical, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Joystick Catalog Number 188083 Model Code M30I-FWRJS2V EAN 4015081857616 Product Length/Depth 36 mm Product Height 93 mm Product Width 46 mm Product Weight 0.06 kg

Certifications VDE 0660

IEC/EN 60947 Features & Functions

Bezel color Stainless steel Bezel material Metal Fitted with: Front ring

Filament bulb (24 V)

Metal shaft General

Degree of protection IP66

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 2000 Operations/h
Product Category RMQ-Titan Size Front dimensions: Ø 36 mm Type Joystick Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Electrical rating
Rated operational current (Ie) at AC-21, 400 V, 415 V 0 A Communication
Connection to SmartWire-DT With SWD-RMQ connections
Yes Actuator
Actuating force 5 N Actuator function Maintained
Vertical Number of actuation directions 2 Contacts
Force for positive opening - min 0 N
ETIM for 188083 Low-voltage industrial controls and switchgear (EC000632)
Feature Name
Feature Value
Rated operation current Ie at AC-21, 400 V (EF002417)
0 A
Centre mounting, hole diameter (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWRJS2V with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.