

INDUSTRIAL COMPONENT DATA

M30I-FWRS*-MS*-* 188140 Y7-188140 EATON ELECTRIC

Key-operated push-buttons, flat front, not master-key syste..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWRS*-MS*-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWRS*-MS*-*
Catalog number	Y7-188140
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-EAF125078D
Generated	2026-08-04

Product Overview

Key-operated push-buttons, flat front, not master-key system compatible, 2 positions, maintained, MS selectable
M30I-FWRS*-MS*-*

Eaton Moeller® series M30 Key-operated actuator, Flat Front, maintained, Select from 2 or 3 positions, MS1-MS20: Key withdrawable: Selectable, Bezel: stainless steel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, selectable, Not suitable for master key systems, selectable, Lock mechanism: selectable, individual facility for inscription, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Notes on customized inscription -> Data sheet, additional product information (links), Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 188140 Model Code

M30I-FWRS*-MS*-* Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg

Certifications CSA Class No.: 3211-03

CSA file No. 012528

DNV

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified

ETIM for 188140 Low-voltage industrial controls and switchgear (EC000222)

Feature Name

Feature Value

Number of switch positions (EF000231)

2

Type of control element (EF006976)

Key

Suitable for lighting (EF001142)

No

Colour control element (EF007167)

Black

Colour indicator light cap (EF007165)

Other

Construction type lens (EF006253)

Round

Hole diameter (EF000079)

30 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No

With front ring (EF006014)

Yes

Material front ring (EF005972)

Metal

Colour front ring (EF002429)

Stainless steel

Degree of protection (IP), front side (EF003118)

IP66

Degree of protection (NEMA) (EF011959)

4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWRS*-MS*-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.