

INDUSTRIAL COMPONENT DATA

M30I-FWRS-MS5 188159 Y7-188159 EATON ELECTRIC

Key-operated push-buttons, flat front, not master-key system C..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWRS-MS5



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWRS-MS5
Catalog number	Y7-188159
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-BE08763BBD
Generated	2026-08-03

Product Overview

Key-operated push-buttons, flat front, not master-key system compatible, 2 positions, maintained, MS5
M30I-FWRS-MS5

Key-operated actuator, Flat Front, maintained, 2 positions, MS5, Key withdrawable: 0, I, Bezel: stainless steel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, maintained, Not suitable for master key systems, 2 positions, Lock mechanism: MS5, I, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Key-operated actuator, Flat Front, maintained, 2 positions, MS5, Key withdrawable: 0, I, Bezel: stainless steelKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, maintained, Not suitable for master key systems, 2 positions, Lock mechanism: MS5, I, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

General specifications
Product name Eaton Moeller® series M30 Key-operated actuator
Part no. M30I-FWRS-MS5 EAN4015081858286
Product Length/Depth 36 millimetre
Product height 67 millimetre
Product width 46 millimetre
Product weight 0.06 kilogram
Certifications VDE 0660
IEC/EN 60947
Product Tradename M30
Product Type Key-operated actuator
Product Sub Type None
Catalog Notes Key withdraw convertible with coding adapters M22-XC-...
Not suitable for master key systems
Features & Functions Bezel color Stainless steel
Bezel material Metal
Design Key operation lock mechanism
Fitted with: Front ring
Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Key code MS5
General information Accessories 1 key included with supplied equipment.
Degree of protection NEMA 4X, 13
Degree of protection (front side) IP66
Lifespan, mechanical 100,000 Operations
Openi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWRS-MS5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.