

INDUSTRIAL COMPONENT DATA

M30I-FWRS-MS8 188163 Y7-188163 EATON ELECTRIC

Key-operated push-buttons, flat front, not master-key system C..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWRS-MS8



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWRS-MS8
Catalog number	Y7-188163
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-8EA200DD5C
Generated	2026-08-05

Product Overview

Key-operated push-buttons, flat front, not master-key system compatible, 2 positions, maintained, MS8
M30I-FWRS-MS8

Eaton Moeller® series M30 Key-operated actuator, Flat Front, maintained, 2 positions, MS8, Key withdrawable: 0, I, Bezel: stainless steel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, maintained, Not suitable for master key systems, 2 positions, Lock mechanism: MS8, I, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 key-operated actuator

Catalog Number 188163

Model Code M30I-FWRS-MS8

EAN 4015081858323

Product Length/Depth 36 mm

Product Height 67 mm

Product Width 46 mm

Product Weight 0.06 kg

Certifications VDE 0660

IEC/EN 60947

CSA file No. 012528

CSA Class No.: 3211-03

DNV

UL File No.: E29184

GL

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE marking

UL Category Control No.: NKCR

UL Listed

CSA certified

Product specifications

Type Key-operated button

Accessories 1 key included with supplied equipment.

Actuator color Black

Actuator function Key withdrawable in position 1

Switching function latching

Key withdrawable in position 0

Maintained

10.10 Temperature rise Not applicable.

10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWRS-MS8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.