

INDUSTRIAL COMPONENT DATA

M30I-FWRS3-MS*-A* 188143 Y7-188143 EATON ELECTRIC

Key-operated push-buttons, flat front, not master-key syst..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWRS3-MS*-A*



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWRS3-MS*-A*
Catalog number	Y7-188143
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-4597D2959A
Generated	2026-08-04

Product Overview

Key-operated push-buttons, flat front, not master-key system compatible, 3 positions, maintained, MS selectable
M30I-FWRS3-MS*-A*

Eaton Moeller® series M30 Key-operated actuator, Flat Front, maintained, 3 positions, MS1-MS20: Key withdrawable:
selectable, Bezel: stainless steel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, maintained, Not
suitable for master key systems, 3 positions, Lock mechanism: selectable, selectable, Degree of Protection: IP64, Front ring
stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, Instructions:
Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding
adapters M22-XC-..., with plunger bridge for the middle contact, With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree
of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M30 Key-operated actuator Catalog Number 188143 Model Code

M30I-FWRS3-MS*-A* Product Length/Depth 36 mm Product Height 67 mm Product Width 46 mm Product Weight 0.06 kg

Certifications IEC/EN 60947

VDE 0660 Features & Functions

Bezel color Stainless steel Bezel material Metal Design Key operation lock mechanism Fitted with: Plunger bridge for the

middle contact

Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Key code Selectable

General

Accessories 1 key included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side) IP64 Lifespan, mechanical 100,000 Operations Opening diameter 30 mm Operating frequency 100 Operations/h Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front dimensions: Ø 36 mm Switching angle 60 ° Type Key-operated button Ambient conditions, mechanical Mounting position As required Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuator color Black Actuator function Switching function latching

Key wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWRS3-MS*-A* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.