

INDUSTRIAL COMPONENT DATA

M30I-FWS3-SA(*)-* 188172 Y7-188172 EATON ELECTRIC

Key-operated push-buttons, flat front, master-key system c..

Brand: EATON - MOELLER | Manufacturer Part Number: M30I-FWS3-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M30I-FWS3-SA(*)-*
Catalog number	Y7-188172
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-336B819DC9
Generated	2026-08-05

Product Overview

Key-operated push-buttons, flat front, master-key system compatible, 3 positions, momentary

M30I-FWS3-SA(*)-*

Key-operated actuator, RMQ-Titan, Key operation lock mechanism, momentary, Suitable for master key systems, 3 positions, Front ring stainless steel

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, momentary, Suitable for master key systems, 3 positions, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, RMQ-Titan, Key operation lock mechanism, momentary, Suitable for master key systems, 3 positions, Front ring stainless steelKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operation lock mechanism, momentary, Suitable for master key systems, 3 positions, Degree of Protection: IP64, Front ring stainless steel, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: Ø 36mm, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP64Delivery program

Product rangeRMQ-TitanBasic functionKey-operated buttonsSingle unit/Complete unitSingle unitDesignKey operation lock mechanismmomentaryFunction: [= spring-return]40°40°Suitable for master key systems3 positionsKey withdrawable in position0Degree of ProtectionIP64Front ringFront ring stainless steelConnection to SmartWire-DTyes

with SWD-RMQ connections Front dimensions Ø 36mm Information about equipment supplied with two keys Technical data
General Standards IEC/EN 60947
VDE 0660 Lifespan, mechanical [Operations] > 0.1 x 10⁶ Operating frequency [Operations/h]? 100 Operating torque? 0.5
Nm Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP64 Ambient temperature Open-25 - +70 °C Mounting position As
required Mechanical shock resistance 15
Shock duration 11 ms
Sinusoidal
according to IEC 60068-2-27 g shipping classification DNV
GL Design verification as per IEC/EN 61439
Operating ambient temperature min. -25 °...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30I-FWS3-SA(*)-* with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.