

## INDUSTRIAL COMPONENT DATA

# M30S-PVL30 197549 Y7-197549 EATON ELECTRIC Emergency Stop Mini Pushbutton D 30 mm Luminous Unlocking by

Brand: EATON - MOELLER | Manufacturer Part Number: M30S-PVL30



|                 |                                        |
|-----------------|----------------------------------------|
| Manufacturer    | EATON - MOELLER                        |
| MPN / Reference | M30S-PVL30                             |
| Catalog number  | Y7-197549                              |
| Category        | Front element for mushroom push-button |
| Minimum order   | 1 Pcs                                  |
| Document ID     | EO-463F31C198                          |
| Generated       | 2026-08-06                             |

## Product Overview

Emergency Stop Mini Pushbutton; D=30 mm; Luminous; Unlocking by M30S-PVL30

HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, Pull-to-release function

HALT/STOP-Button, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 30 mm, Illumination: Illuminated with LED element, Pull-to-release function, Color Mushroom head: Black, Color Base: yellow, Color RAL Value: RAL 9005, Degree of Protection: IP65, IP66, IP69, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 35, Instructions: Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED..., When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item separately., Standards: EN 50581:2012 , EN 60947-5-1:2017, EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017, EN ISO 13850:2015, 2006/42/EC Machinery Directive

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, Pull-to-release functionHALT/STOP-Button, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 30 mm, Illumination: Illuminated with LED element, Pull-to-release function, Color Mushroom head: Black, Color Base: yellow, Color RAL Value: RAL 9005, Degree of Protection: IP65, IP66, IP69, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 35, Instructions: Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED..., When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item

separately., Standards: EN 50581:2012 , EN 60947-5-1:2017, EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017, EN ISO 13850:2015, 2006/42/EC Machinery Directive

General specificationsProduct nameEaton Moeller® series M30 Emergency stop/emergency switching off pushbuttonPart no.M30S-PVL30EAN4015081942657Product Length/Depth30 millimetreProduct height32 millimetreProduct width30 millimetreProduct weight0.03 kilogramCertificationsCSA

CCC

EN 60947-5-1

CE

EN ISO 13850

EN 50581

EAC

Machines 2006/42/EGProduct TradenameM30Product TypeEmergency stop/emergency switching off pushbuttonProduct Sub TypeNoneFeatures & FunctionsBezel colorOtherBase colorYellowBezel materialOtherDesignClassical Mushroom-shapedIlluminationIlluminated with LED elementRAL-number9005Unlocking methodPull-releaseGeneral informationDegree of protectionNEMA 4X IP6...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M30S-PVL30 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.