

INDUSTRIAL COMPONENT DATA

T5-7-8350/V/SVB-SW 094661 Y7-94661 EATON ELECTRIC Main switch, 14-pole, 100 A, STOP function, 90 °, rear mou..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-7-8350/V/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5-7-8350/V/SVB-SW
Catalog number	Y7-94661
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A06E68C033
Generated	2026-08-06

Product Overview

Main switch, 14-pole, 100 A, STOP function, 90 °, rear mounting

General Switch 14 poles 100 A 90° Bottom panel mount Handle

Eaton Moeller® series T5 Main switch, T5, 100 A, rear mounting, 7 contact unit(s), 14-pole, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5, Stop Function: STOP function, With black rotary handle and locking ring, 14-pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Main switch Catalog Number 094661 Model Code T5-7-8350/V/SVB-SW EAN 4015080946618 Product Length/Depth 237 mm Product Height 88 mm Product Width 88 mm Product Weight 1.2 kg

Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 094661 Low-voltage industrial controls and switchgear (EC000216)

Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current I_{cw} (EF007050)
1.7 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current I_q (EF001444)
2 kA
Number of poles (EF001391)
14
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device const...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-7-8350/V/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.