

INDUSTRIAL COMPONENT DATA

**T3-1-8200/EA/SVB-SW 068949 Y7-68949 EATON ELECTRIC
Main switch, 1 pole, 32 A, STOP function, 90 °, Lockable ..**

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-8200/EA/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-8200/EA/SVB-SW
Catalog number	Y7-68949
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D1EC0D5A8E
Generated	2026-08-06

Product Overview

Main switch, 1 pole, 32 A, STOP function, 90 °, Lockable in the 0 (Off) position, flush mounting

General Switch 1 pole 32 A 90° Flush Mount Black Handle

Main switch, T3, 32 A, flush mounting, 1 contact unit(s), 1 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: STOP function, With black rotary handle and locking ring, 1 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T3, 32 A, flush mounting, 1 contact unit(s), 1 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T3, Stop Function: STOP function, With black rotary handle and locking ring, 1 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3 Delivery program
Product range Main switch

maintenance switch

Repair switch Part group reference T3 Stop Function STOP function With black rotary handle and locking ring Number of poles 1 pole Locking facility Lockable in the 0 (Off) position Degree of Protection Front IP65 Design flush mounting Contact sequence Switching angle 90 ° Design number 8200 Function Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 15 kW Rated uninterrupted current [Iu] 32 A Note on rated uninterrupted current Iu Rated uninterrupted current Iuis specified for max. cross-section. Number of contact units 1 contact unit(s) Technical data
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-8200/EA/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.