

INDUSTRIAL COMPONENT DATA

IS-125/3 276288 Y7-276288 EATON ELECTRIC Main switch, 240 V, 125A, 3HP

Brand: EATON - MOELLER | Manufacturer Part Number: IS-125/3



Manufacturer	EATON - MOELLER
MPN / Reference	IS-125/3
Catalog number	Y7-276288
Category	Main switch for distribution board
Minimum order	1 Pcs
Document ID	EO-492F17854F
Generated	2026-08-05

Product Overview

Main switch, 240 V, 125A, 3HP

IS-125/3

Main load disconnecter Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 125 A, 3P

Switch with isolating function, type conform to IEC/EN 60947-3, contact with high wear resistance, jump activation, thumb-grip colour black, terminal cross-section 50mm², busbar compatible with Xpole protection switching devices when using the jaw clamp in combination with standard fork busbars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series IS Disconnecter Catalog Number 276288 Model Code IS-125/3 EAN 4015082762889

Product Length/Depth 60 mm Product Height 80 mm Product Width 53.1 mm Product Weight 0.314 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type IS. Main load disconnecter switch Application Switchgear for industrial and advanced commercial applications Degree of protection IP40

IP10 Terminals Lift terminal Equipment heat dissipation, current-dependent 16.5 W Imprint/indication Symbol "arrows" Lamp socket Other Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Built-in depth 69.5 mm

Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 6.2 W Lamp power 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 3 Amperage rating 125 A Color calotte Other Switch type Other Rated short-time withstand current (Icw) 2 kA Voltage type AC Lamp type Other Number of contacts (normally open contacts) 3 Rated operational current for specified heat dissipation (In) 125 A Rated operational voltage (Ue) - max 415 V Rated switching capacity 10 kA Static heat dissipation, non-current-dependent 0 W Voltage rating - min 240 V Width in number of modular spacings 3 Number of poles Three-pole
ETIM for 276288 Modular devices for distribution board/surface mounting (EC001545)
Feature Name
Feature Value
Switching function (EF000189)
Other
Numb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IS-125/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.