

INDUSTRIAL COMPONENT DATA

T0-2-113/EA/SVB-SW 007952 Y7-7952 EATON ELECTRIC Main switch, 3 pole + 1 N/C, 20 A, STOP function, 90 °, flu..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-113/EA/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-113/EA/SVB-SW
Catalog number	Y7-7952
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-04B3619A8D
Generated	2026-07-29

Product Overview

Main switch, 3 pole + 1 N/C, 20 A, STOP function, 90 °, flush mounting

General switch; 3-pole + 1 NC; 20 A; Lever Black; Lockable in position (OFF); 90 °; Mounting

Eaton Moeller® series T0 Main switch, T0, 20 A, flush mounting, 2 contact unit(s), 3 pole, 1 N/C, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Main switch Catalog Number 007952 Model Code T0-2-113/EA/SVB-SW EAN 4015080079521 Product Length/Depth 111 mm Product Height 74 mm Product Width 65 mm Product Weight 0.108 kg

Certifications CSA Class No.: 3211-05

UL

CSA File No.: 012528

UL 60947-4-1

UL File No.: E36332

CSA
VDE 0660
IEC/EN 60947-3
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
IEC/EN 60204
UL Category Control No.: NLRV
IEC/EN 60947
CE Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 007952 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
20 A
Rated permanent current at AC-21, 400 V (EF009165)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Rated short-time withstand current Icw (EF007050)
0.32 kA
Rated operation power at AC-23, 400 V (EF007027)
5.5 kW
Switching power at 400 V (EF009166)
5.5 kW
Conditioned rated short-circuit current Iq (EF001444)
6 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normall...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-113/EA/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.