

INDUSTRIAL COMPONENT DATA

P3-100/M4/SVB-SW/HI11 172823 Y7-172823 EATON ELECTRIC Main switch, 3 pole + 1 N/O + 1 N/C, 100 A, STOP funct..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-100/M4/SVB-SW/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P3-100/M4/SVB-SW/HI11
Catalog number	Y7-172823
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C0E20E1930
Generated	2026-08-05

Product Overview

Main switch, 3 pole + 1 N/O + 1 N/C, 100 A, STOP function, Lockable in the 0 (Off) position, rear mounting, with 400 mm metal shaft

P3-100/M4/SVB-SW/HI11

Main switch, P3, 100 A, rear mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, Notes: Handle only for use with extension shaft P1/P3-400 (172844)., Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: Iu = 100 A, Standards: IEC/EN 60947, VDE 0660 , IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Main switch, P3, 100 A, rear mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: P3, Stop Function: STOP function, With black rotary handle and locking ring, Notes: Handle only for use with extension shaft P1/P3-400 (172844)., Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user.,

3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3 Delivery program

Product range Main switch
maintenance switch

Repair switch Part group reference P3 Stop Function STOP function With black rotary handle and locking ring Notes Handle only for use with extension shaft P1/P3-400 (172844). Information about equipment supplied Auxiliary contact or neutral conductor fitted by user. Notes With metal shaft for a control panel depth of 400 mm Number of poles 3 pole Auxiliary contacts 1 N/O 1 N/C Locking facility Lockable in the 0 (Off) position Degree of Protection Front IP65 Design rear mounting Contact sequence Function Motor rating AC-23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-100/M4/SVB-SW/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.