

## INDUSTRIAL COMPONENT DATA

# P1-25/M4/K1-PR/N 172773 Y7-172773 EATON ELECTRIC Main switch, 3 pole + N, 25 A, Emergency-Stop function, Loc..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/M4/K1-PR/N



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-25/M4/K1-PR/N    |
| Catalog number  | Y7-172773           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-7B42D171FA       |
| Generated       | 2026-08-03          |

## Product Overview

Main switch, 3 pole + N, 25 A, Emergency-Stop function, Lockable in the 0 (Off) position, rear mounting, with 400 mm metal shaft

P1-25/M4/K1-PR/N

Main switch, P1, 25 A, rear mounting, 3 pole + N, Emergency switching off function, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

Main switch, P1, 25 A, rear mounting, 3 pole + N, Emergency switching off function, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mmMain switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Interlockable, Emergency switching off function, Fitted with: Metal shaft for a control panel depth of 400 mm, Red rotary handle and yellow locking ring, Mounting method: Rear mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

General specificationsProduct nameEaton Moeller® series P1 Main switchPart

no.P1-25/M4/K1-PR/NEAN4015081693917Product Length/Depth340 millimetreProduct height70 millimetreProduct width71 millimetreProduct weight0.335 kilogramCertificationsIEC/EN 60947-3

IEC/EN 60947

VDE 0660

IEC/EN 60204Product TradenameP1Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time

Withstand Current (Icw) for a time of 1 second  
Features & Functions  
Version as emergency stop installation  
Version as maintenance-/service switch  
Version as main switch  
Fitted with: Metal shaft for a control panel depth of 400 mm  
Red rotary handle and yellow locking ring  
Functions  
Interlockable  
Emergency switching off function  
Locking facility  
Lockable in the 0 (Off) position  
Number of poles 4  
General information  
Accessories  
Auxiliary contact fitted by user.  
Degree of protection NEMA 12  
Degree of protection (front side) IP65  
Lifespan, mechanical 300,000 Operations  
Mounting method Rear mounti...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/M4/K1-PR/N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.